

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Patent Application Transmittal

Assistant Commissioner of Patents
Washington, DC 20231
Sir:

Transmitted herewith for filing is the Patent Application of:

Inventor: Steven D. Ims, Yongcheng Li, Yih-Shin Tan, and Brian Webb

For: Legacy Host System Hot Link Modeling and Navigation

Enclosed are:

☒ 11 Sheets of Formal Drawings

☒ An assignment of the invention to International Business Machines, Armonk, NY 10504

☒ Declaration and Power of Attorney

The filing fee has been calculated as shown below:

Other Than Small Entity

For:	No. Filed	No. Extra	Rate	Fee
Basic Fee				\$ 760.00
Total Claims	37-20 =	17	17x \$ 18.00=	\$ 306.00
Indep. Claims	3 - 3 =	0	0 x \$ 78.00=	\$.00
Multiple Dependent Claim Presented			\$260.00	\$.00
			TOTAL	\$1,066.00


Deposit Account Authorization:

☒ Please charge Deposit Account No. 09-0461 in the amount of \$1,066.00. A duplicate copy of this sheet is enclosed.
☒ The Commissioner is hereby authorized to charge payment of the following fees associated with this communication or credit any overpayment to Deposit Account No. 09-0461. A duplicate copy of this sheet is enclosed.
☒ Any additional filing fees required under 37 C.F.R. §1.16.
☒ Any patent application processing fees under 37 C.F.R. §1.17.

Date: November 18, 1999

Respectfully submitted,

From: Jeanine S. Ray-Yarletts
IBM Corporation
IPLaw, Dept. T81/Bldg. 062
P.O. Box 12195
Research Triangle Park, NC 27709

By: 
Jeanine S. Ray-Yarletts
Attorney of Record
Reg. No. 39,808

Telephone: 919-543-2541
Fax: 919-254-4330

jc584 U.S. PTO
09/442791
11/18/99

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of: S. D. Ims, et al

Serial No.:

Filed: Herewith

For: Legacy Host System Hot Link Modeling and Navigation

Assistant Commissioner of Patents
Washington, D.C. 20231

EXPRESS MAIL CERTIFICATE

"Express Mail" label number: EK246343682US

Date of Deposit: November 18, 1999

WE REQUEST THE DATE OF DEPOSIT AS THE DATE FILED.

I hereby certify that the following **attached** correspondence comprising:

1. Patent Application Transmittal, in duplicate
2. Patent Application, 27 pages
3. Formal Drawings, 11 sheets
4. Recordation Cover Sheet, in duplicate
5. Assignment
6. Declaration and Power of Attorney
7. Business Reply Postcard

is being deposited with the United States Postal Service Express Mail Post Office to Addressee service under CFR 1.10 on the date indicated above and is addressed to:

**Box Patent Application
Assistant Commissioner of Patents
Washington, D.C. 20231**

Dianne Lane
(Name of person mailing paper or fee)

Dianne Lane

EXPRESS MAIL LABEL NO : EK246343682US DATE OF DEPOSIT: *Nov. 18, 1999*

I hereby certify that this paper and fee are being deposited with the United States Postal Service Express Mail Post Office to Addressee service under 37 CFR §1.10 on the date indicated above and is addressed to the Assistant Commissioner of Patents, Washington, D.C. 20231.

Dianne Lane
NAME OF PERSON MAILING PAPER AND FEE

Dianne Lane
SIGNATURE OF PERSON MAILING PAPER AND FEE

INVENTORS: Steven D. Ims, Yongcheng Li, Yih-Shin Tan, and Brian Webb

LEGACY HOST SYSTEM HOT LINK MODELING AND NAVIGATION

BACKGROUND OF THE INVENTION

1. Technical Field:

The present invention relates generally to computer software and, more specifically, to methods of presenting an Internet style hot linking system to access legacy host system datastream screens.

2. Description of Related Art:

The Internet, also referred to as an "internetwork", is a set of computer networks, possibly dissimilar, joined together by means of gateways that handle data transfer and the conversion of messages from the sending network to the protocols used by the receiving network (with packets if necessary). When capitalized, the term

"Internet" refers to the collection of networks and gateways that use the TCP/IP suite of protocols.

The Internet has become a cultural fixture as a source of both information and entertainment. Many businesses are creating Internet sites as an integral part of their marketing efforts, informing consumers of the products or services offered by the business or providing other information seeking to engender brand loyalty. Many federal, state, and local government agencies are also employing Internet sites for informational purposes, particularly agencies which must interact with virtually all segments of society such as the Internal Revenue Service and secretaries of state. Providing informational guides and/or searchable databases of online public records may reduce operating costs. Further, the Internet is becoming increasingly popular as a medium for commercial transactions.

Currently, the most commonly employed method of transferring data over the Internet is to employ the World Wide Web environment, also called simply "the Web". Other Internet resources exist for transferring information, such as File Transfer Protocol (FTP) and Gopher, but have not achieved the popularity of the Web. In the Web environment, servers and clients effect data transaction using the Hypertext Transfer Protocol (HTTP), a known protocol for handling the transfer of various data files (e.g., text, still graphic images, audio, motion video, etc.). The information in various data files is formatted for presentation to a user by a standard page description language, the Hypertext Markup Language (HTML). In addition to basic presentation formatting, HTML allows developers to specify "links" to other Web resources identified by a Uniform Resource Locator (URL). A URL is a special syntax identifier defining a communications path to specific information. Each logical block of information accessible to a client, called a "page" or a "Web page", is identified by a URL. The URL provides a universal, consistent method for finding

and accessing this information, not necessarily for the user, but mostly for the user's Web "browser". A browser is a program capable of submitting a request for information identified by a URL at the client machine. Retrieval of information on the Web is generally accomplished with an HTML-compatible browser. The Internet also is widely used to transfer applications to users using browsers. With respect to commerce on the Web, individual consumers and business use the Web to purchase various goods and services. In offering goods and services, some companies offer goods and services solely on the Web while others use the Web to extend their reach.

However, many computer resources were written before the Internet had become a cultural fixture and without contemplating adaptation of the application, service or data to an Internet connected world. Thus, many computer services (legacy host systems) to which users desire access must be reformatted such that they are readable and useable by web browsers, since this is one of the most convenient and common methods of accessing information via the Internet.

Even with reformatting, however, users were required to be trained or otherwise be familiar with the particular commands necessary to navigate through the various screens contained within these legacy host systems. If users desire access to several or many of these systems, remembering the commands associated with each system becomes burdensome. Furthermore, many people may desire one time or occasional access to systems. Thus, knowledge of the particular commands is even more burdensome to these people. Therefore, a method of accessing and navigating through various screens of a legacy host system without requiring knowledge of service specific commands is desirable. Furthermore, it is desirable to have such a system that is compatible with currently available browsers and uses a system of graphically displayed hyperlinks to which most users have grown accustomed.

SUMMARY OF THE INVENTION

5 The present invention provides a method and apparatus for navigating screens in a legacy host system. In a preferred embodiment, requests for specific legacy host screens are received by a server. The server then navigates to the appropriate screen within the legacy host system and retrieves the host screen. If there are intermediate screens which need to be navigated to get to the host screen, the server does so, but does not send these intermediate screens to the user if not needed by the user, thus saving bandwidth and time for the user. If variable data need be entered to access the host screen, the server sends the user a submittable form on which to enter the appropriate information, which, once entered and sent to the server, is used by the server to retrieve the host screen. Once the host screen has been retrieved, the server formats it into a web page format using a hypertext language such as extensible markup language (XML) or hypertext markup language (HTML) and sends the screen to the user. Selectable links are displayed to the user to allow the user to request other screens within the legacy host system.

BRIEF DESCRIPTION OF THE DRAWINGS

20 The novel features believed characteristic of the invention are set forth in the appended claims. The invention itself, however, as well as a preferred mode of use, further objectives and advantages thereof, will best be understood by reference to the following detailed description of an illustrative embodiment when read in conjunction with the accompanying drawings, wherein:

Figure 1 depicts a system diagram illustrating a distributed data processing system in which a the present invention may be implemented;

Figure 2 depicts a block diagram of a data processing system that may be implemented as a server in accordance with the present invention;

Figure 3 depicts a block diagram of a data processing system in which the present invention may be implemented;

Figure 4 depicts a block diagram of a browser program in accordance with a preferred embodiment of the present invention;

Figure 5 depicts a block diagram illustrating a system for navigating a legacy host system according to the present invention;

Figure 6 depicts an example of a browser window containing links to screens within a legacy host system in accordance with the present invention;

Figures 7A-7C depict an example of a macro for navigating to various screens within a legacy host system in accordance with the present invention;

Figure 8 depicts a flowchart illustrating an overview of a method on a server for navigating and retrieving a legacy host screen according to the present invention; and

Figure 9 depicts a flowchart illustrating a method of navigating and viewing legacy host screens from the perspective of a client computer in accordance with the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

With reference now to the figures, and in particular with reference to **Figure 1**, a system diagram illustrating a distributed data processing system in which a the present invention may be implemented is depicted.

Distributed data processing system **100** is a plurality of interconnected heterogeneous networks in which the present invention may be implemented. As illustrated, distributed data processing system **100** contains an Internet Protocol (IP) network **102**, a Local Area Network (LAN) / Wide Area Network (WAN) **104**, the Public Switched Telephone Network (PSTN) **109**, a cellular wireless network **112**, and a satellite communication network **116**. Networks **102**, **104**, **109**, **112**, and **116** may include permanent connections, such as wire or fiber optic cables, or temporary connections made through telephone connections.

IP network **102** may be the publicly available IP network (the Internet), a private IP network, or a combination of public and private IP networks. In any case, IP network **102** operates according to the Internet Protocol and routes packets among its many switches and through its many transmission paths. IP networks are generally known in the art to be expandable, fairly easy to use and heavily supported. Coupled to IP network **102** is a Domain Name Server (DNS) **108** to which queries may be sent, such queries each requesting an IP address based upon a Uniform Resource Locator (URL). IP network **102** supports 32 bit IP addresses as well as 128 bit IP addresses, which are currently in the planning stage.

In the depicted example, server **150** is connected to IP network **102**, along with storage unit **154**. In addition, clients **152** and **156** are also connected to IP network **102**. These clients, **152** and **156**, may be, for example, personal computers or network computers. For purposes of this application, a network computer is any computer coupled to a network, which receives a program or other application from another computer coupled to the network. In the depicted example, server **150** provides data, such as boot files, operating system images and applications, to clients **152** and **156**. Server **150** may provide data to clients connected to any of networks **104**, **109**, **112**, or **116** as well.

LAN/WAN **104** couples to IP network **102** via a proxy server **106** (or another connection). LAN/WAN **104** may operate according to various communication protocols, such as the Internet Protocol, the Asynchronous Transfer Mode (ATM) protocol, or other known packet switched protocols. Proxy server **106** serves to route data between IP network **102** and LAN/WAN **104**. A firewall that precludes unwanted communications from entering LAN/WAN **104** may also be located at the location of proxy server **106**.

Computer **120** couples to LAN/WAN **104** and supports communications with LAN/WAN **104**. Computer **120** may employ the LAN/WAN and proxy server **106** to communicate with other devices across IP network **102**. Such communications are generally known in the art and will not be further described herein except to expand upon the teachings of the present invention. As is also shown, phone **122** couples to computer **120** and may be employed to initiate IP Telephony communications with another phone or voice terminal using IP Telephony. In such an IP telephony system, a gatekeeper **152** is deployed by a service provider to manage IP telephony for its users. An IP phone **154** connected to IP network **102** (or other phone, e.g., phone **124**) may communicate with phone **122** using IP telephony.

PSTN **109** is a circuit switched network that is primarily employed for voice communications, such as those enabled by a standard phone **124**. However, PSTN **109** also supports the transmission of data. Data transmissions may be supported to a tone based terminal, such as a FAX machine **125**, to a tone based modem contained in computer **126**, or to another device that couples to PSTN **109** via a digital connection, such as an Integrated Services Digital Network (ISDN) line, an Asynchronous Digital Subscriber Line (ADSL), or another digital connection to a terminal that supports such a connection. As illustrated, a voice terminal, such as phone **128**, may couple to PSTN **109** via computer **126** rather than being supported directly by PSTN **109**, as is

the case with phone **124**. Thus, computer **126** may support IP telephony with voice terminal **128**, for example.

Cellular network **112** supports wireless communications with terminals operating in its service area (which may cover a city, county, state, country, etc.). As is known, cellular network **112** includes a plurality of towers, e.g., **130**, that each service communications within a respective cell. Wireless terminals that may operate in conjunction with cellular network **112** include wireless handsets **132** and wirelessly enabled laptop computers **134**, for example. Wireless handsets **132** could be, for example, personal digital assistants, wireless or cellular telephones, or two-way pagers. Cellular network **112** couples to IP network **102** via gateway **114**.

Wireless handsets **132** and wirelessly enabled laptop computers **134** may communicate with cellular network **112** using a wireless application protocol (WAP). WAP is an open, global specification that allows mobile users with wireless devices, such as, for example, mobile phones, pagers, two-way radios, smartphones, communicators, personal digital assistants, and portable laptop computers, to easily access and interact with information and services almost instantly. WAP is a communications protocol and application environment and can be built on any operating system including, for example, Palm OS, EPOC, Windows CE, FLEXOS, OS/9, and JavaOS. WAP provides interoperability even between different device families.

WAP is the wireless equivalent of Hypertext Transfer Protocol (HTTP) and Hypertext Markup Language (HTML). The HTTP-like component defines the communication protocol between the handheld device and a server or gateway. This component addresses characteristics that are unique to wireless devices, such as data rate and round-trip response time. The HTML-like component, Wireless Markup Language (WML), defines new markup and scripting languages for displaying

information to and interacting with the user. This component is highly focused on the limited display size and limited input devices available on small, handheld devices. For example, a typical cell phone may have only a 4x10-character display with 16-gray levels and only a numeric keypad plus up/down volume keys.

5 Cellular network **112** operates according to an operating standard, which may be the Advanced Mobile Phone System (AMPS) standard, the Code Division Multiple Access (CDMA) standard, the Time Division Multiple Access (TDMA) standard, or the Global System for Mobile Communications or Groupe Speciale Mobile (GSM), for example. Independent of the standard(s) supported by cellular network **112**, cellular network **112** supports voice and data communications with terminal units, e.g., **132** and **134**.

10 Satellite network **116** includes at least one satellite dish **136** that operates in conjunction with a satellite **138** to provide satellite communications with a plurality of terminals, e.g., laptop computer **142** and satellite handset **140**. Satellite handset **140** could also be a two-way pager. Satellite network **116** may be serviced by one or more geosynchronous orbiting satellites, a plurality of medium earth orbit satellites, or a plurality of low earth orbit satellites. In any case, satellite network **116** services voice and data communications and couples to IP network **102** via gateway **118**.

15
20 **Figure 1** is intended as an example and not as an architectural limitation for the processes of the present invention. For example, distributed data processing system **100** may include additional servers, clients, and other devices not shown.

25 Referring to **Figure 2**, a block diagram of a data processing system which may be implemented as a server, such as server **150** in **Figure 1**, is depicted in accordance with the present invention. Data processing system **200** may be a symmetric multiprocessor (SMP) system including a plurality of processors **202** and **204** connected to system bus **206**. Alternatively, a single processor system may be

employed. Also connected to system bus **206** is memory controller/cache **208**, which provides an interface to local memory **209**. I/O bus bridge **210** is connected to system bus **206** and provides an interface to I/O bus **212**. Memory controller/cache **208** and I/O bus bridge **210** may be integrated as depicted.

5 Peripheral component interconnect (PCI) bus bridge **214** connected to I/O bus **212** provides an interface to PCI local bus **216**. A number of modems **218-220** may be connected to PCI bus **216**. Typical PCI bus implementations will support four PCI expansion slots or add-in connectors. Communications links to network computers **152** and **156** in **Figure 1** may be provided through modem **218** and network adapter **220** connected to PCI local bus **216** through add-in boards.

10 Additional PCI bus bridges **222** and **224** provide interfaces for additional PCI buses **226** and **228**, from which additional modems or network adapters may be supported. In this manner, server **200** allows connections to multiple network computers. A memory mapped graphics adapter **230** and hard disk **232** may also be connected to I/O bus **212** as depicted, either directly or indirectly.

15 Those of ordinary skill in the art will appreciate that the hardware depicted in **Figure 2** may vary. For example, other peripheral devices, such as optical disk drives and the like, also may be used in addition to or in place of the hardware depicted. The depicted example is not meant to imply architectural limitations with respect to the present invention.

20 The data processing system depicted in **Figure 2** may be, for example, an IBM RS/6000, a product of International Business Machines Corporation in Armonk, New York, running the Advanced Interactive Executive (AIX) operating system or an Intel based machine running a Windows NT operating system.

25 With reference now to **Figure 3**, a block diagram of a data processing system in which the present invention may be implemented is illustrated. Data processing

system 300 is an example of a client computer. Data processing system 300 employs a peripheral component interconnect (PCI) local bus architecture. Although the depicted example employs a PCI bus, other bus architectures, such as Micro Channel and ISA, may be used. Processor 302 and main memory 304 are connected to PCI local bus 306 through PCI bridge 308. PCI bridge 308 may also include an integrated memory controller and cache memory for processor 302. Additional connections to PCI local bus 306 may be made through direct component interconnection or through add-in boards. In the depicted example, local area network (LAN) adapter 310, SCSI host bus adapter 312, and expansion bus interface 314 are connected to PCI local bus 306 by direct component connection. In contrast, audio adapter 316, graphics adapter 318, and audio/video adapter (A/V) 319 are connected to PCI local bus 306 by add-in boards inserted into expansion slots. Expansion bus interface 314 provides a connection for a keyboard and mouse adapter 320, modem 322, and additional memory 324. In the depicted example, SCSI host bus adapter 312 provides a connection for hard disk drive 326, tape drive 328, CD-ROM drive 330, and digital video disc read only memory drive (DVD-ROM) 332. Typical PCI local bus implementations will support three or four PCI expansion slots or add-in connectors.

An operating system runs on processor 302 and is used to coordinate and provide control of various components within data processing system 300 in **Figure 3**. The operating system may be a commercially available operating system, such as OS/2, which is available from International Business Machines Corporation. "OS/2" is a trademark of International Business Machines Corporation. An object oriented programming system, such as Java, may run in conjunction with the operating system, providing calls to the operating system from Java programs or applications executing on data processing system 300. Instructions for the operating system, the object-oriented operating system, and applications or programs are located on a

storage device, such as hard disk drive **326**, and may be loaded into main memory **304** for execution by processor **302**.

Those of ordinary skill in the art will appreciate that the hardware in **Figure 3** may vary depending on the implementation. For example, other peripheral devices, such as optical disk drives and the like, may be used in addition to or in place of the hardware depicted in **Figure 3**. The depicted example is not meant to imply architectural limitations with respect to the present invention. For example, the processes of the present invention may be applied to multiprocessor data processing systems.

Turning next to **Figure 4**, a block diagram of a browser program is depicted in accordance with a preferred embodiment of the present invention. Browser **400** includes a user interface **402**, which is a graphical user interface (GUI) that allows the user to interface or communicate with browser **400**. This interface provides for selection of various functions through menus **404** and allows for navigation through the navigation button **406** or selections. For example, menu **404** may allow a user to perform various functions, such as saving a file, opening a new window, displaying a history, and entering a URL. Navigation **406** allows for a user to navigate various pages and to select web sites for viewing. For example, navigation **406** may allow a user to see a previous page or a subsequent page relative to the present page. Preferences may be set through preferences **408**.

Communications **410** is the mechanism with which browser **400** receives documents and other resources from a network such as the Internet. Further, communications **410** is used to send or upload documents and resources onto a network. In the depicted example, communication **410** uses HTTP. However, other protocols are possible. Documents that are received by browser **400** are processed by language interpretation **412**, which includes an HTML unit **414**. Language

interpretation **412** will process a document for presentation on graphical display **418**. In particular, HTML statements are processed by HTML unit **414** for presentation.

Graphical display **418** includes layout unit **420**, rendering unit **422**, and window management **424**. These units are involved in presenting web pages to a user based on results from language interpretation **412**.

Browser **400** is presented as an example of a browser program in which the present invention may be embodied.

Browser **400** is not meant to imply architectural limitations to the present invention. Presently available browsers may include additional functions not shown or may omit functions shown in browser **400**. As used herein, the term "browser" encompasses any software application used to view or navigate for information or data (e.g., something that assist a user to browser) in a distributed data base where the distributed database is typically the internet or World Wide Web.

Referring now to **Figure 5**, a block diagram illustrating a system for navigating a legacy host system is depicted according to the present invention. A navigation system **510** resides on a web server **508** with a connection to a legacy host system **506**. Web server **508** may be implemented as server **150** in **Figure 1** with legacy host system **506** located on database **154** wherein the connection between web server **508** and legacy host system **506** is provided by IP Network **102**. A user communicates with navigation system **510** via browser **502** which may reside on a client such as client **108** in **Figure 1** and which may be implemented as browser **400** in **Figure 4**.

Navigation system **510** renders a "system" of host screens into a web page of hot links and sends them to browser **502**. A user initially acquires access to a legacy host screen by typing in a universal resource locator (URL) that is the host linking application address of server **508** into browser **502**. In this example, the user types

the URL <http://www.mycompany.com/hostlinker> to access server **502**, which provides access to legacy host system **506**. Once the initial URL is accessed, a new session is open and the first screen is formatted into HTML with hot links and user information in either a cookie or form data is passed back to the browser along with this first screen. This first screen is usually a logon screen. The user information is sent back and forth with each request and helps to map requests to host sessions open on the server. All the hot links in the pages sent to the user point back to <http://www.mycompany.com/hostlinker>.

Browser **502** displays the list of HREF style hot links **522** that represent each screen in the host system **506** as received from navigation system **510**. An example of such a web page style navigation window is illustrated in **Figure 6**. Each screen within the host system to which a user might wish to navigate is represented by a selectable “hot” link **602-612**, which, when selected, such as by clicking with a mouse, sends a request to navigation system **510** to retrieve the appropriate screen within host system **506**.

Note, if variable data is needed to navigate from screen to screen, the link will be presented as a submittable form and will contain text fields the user should fill in for the variable data. There are two possible options the user can choose with respect to entering data as illustrated in **Figure 6**.

In one option, as illustrated in callup section **614**, the submittable form is presented to the user along with the links such that if the user wishes to retrieve that particular screen, the user must enter the data in the submittable form. In another option as illustrated in section **616**, the links are presented to the user without a submittable form but with an indication that user input will be required to access those screens. If the user selects one of these screens, then the navigation system **510** will generate and send a submittable form to the user for entry of the variable data

needed to access the legacy host screen specified by the user. Once the user has entered the data, he will select a submit or search option to send the entered data back to navigation system **510**, which will use the variable data to access the requested legacy host screen.

Referring still to **Figure 6**, the current screen within the legacy host system is displayed to the user in box **618** within the frame window. The contents of box **618** change as the user navigates within the legacy host system. In an alternate embodiment, the contents of the current screen from the legacy host system are displayed in a separate frame window from the navigator window **600**.

Referring again to **Figure 5**, once a link from host screen links **522** is selected, a request for a new screen **520** is sent to navigation system **510** via a hypertext transfer protocol (HTTP) datastream **516**. As the request for a new screen is sent, a hidden applet **504** within browser **502** is also notified **518** of the request for a new screen and opens a socket connection with datastream object **512** within server **508**.

Once navigation system **510** receives the request for a host screen, it navigates to the host screen. If a direct connection exists between the current screen and the host screen, then a macro bean within navigation system **510** enters the appropriate data to access the host screen. If several screens must be accessed in order to access the host screen, then the appropriate entries are made at each screen such that access to the host screen is attained. If variable data is needed to proceed through some of the intermediate screens or for direct access to the host screen, that variable data is acquired from the user as mentioned above either through sending a submittable form requesting the appropriate data or by having the submittable form as part of the initial screen containing the links to the various screens within the legacy host system.

The links between each screen in the macro within navigation system **510** are not merely connections to verify a next screen as current systems provide. Rather, the

macro bean within the navigation system **510** contains the intelligence to record and use the links for jumping over multiple screens to get to the target screen if the ultimate connections exists and then stopping at the target screen. In other words, each next screen specified in a macro screen block will contain default actions for navigating from the current screen block to the next. An example of this can be seen with the <nextscreen> tags in the sample macro depicted in **Figures 7A-7C** which will be discussed in more detail below.

Once access to the host screen has been acquired, the host screen is retrieved from legacy host system **506** and reformatted into a hypertext language such as an extensible markup language (XML) or a hypertext markup language (HTML) including host links such that the screen may be displayed to the user through browser **502** as a web page. Datastream object **512** notifies hidden applet **504** of a screen update and navigation system **510** sends the requested host screen formatted in a markup language to browser **502** via HTTP datastream **516**. Browser **502** then displays the requested legacy host screen to the user.

Thus, the present invention provides access via the Internet to applications, services and/or data that were created without contemplation of providing these applications, services and/or data to users via the Internet. The present invention also allows visualization/modeling of a legacy host system using the well understood "hot" link paradigm for navigating between screens. Furthermore, the present invention allows the user to browse around screens in the Macro doing away with the concept of playing macros to accomplish specific tasks. In essence, one big macro that represents the entire accessible host system is always playing. Thus, users are allowed to use a legacy host system without training in or knowledge of how to issue the right host commands at the right screens. The user simply browses around the

system much as one would browse around linked Internet pages on the World Wide Web (WWW), concentrating on the data rather than on the navigation.

The present invention also allows the user to skip past several screens, thus having only the screens of interest to the user presented to the user. This is great for palm devices and other wireless devices where bandwidth is at a premium. For example, the user can skip directly from the ready prompt to the puborder search without having to see the five screens in between. Other advantages will be obvious to those skilled in the art.

Referring now to **Figures 7A-7C**, an example of a macro suitable for providing navigation around legacy host system is depicted in accordance with the present invention. In the present example, the macro bean corresponds to the IBM Host On-Demand (HOD) Macro bean. A macro bean is a programming object that, when connected to a host terminal emulator programming object (i.e., IBM HOD's Session bean), automatically navigates through host screens based on the user coded script provided to the Macro bean (i.e., the XML code). Each of blocks **702-718** contains XML code for navigating from a specific screen in the legacy host system to other screens within the legacy host system. Each of blocks **702-718** contain an entry for the screen name, whether the screen is transient, and whether the screen is an entry or an exit screen. Each of blocks **702-718** only executes if the current screen from which a request for a new screen was made corresponds to the screen name tag at the top of the block. The transient tag indicates whether the screen is displayed to the user. If the transient tag is true, then the appropriate entries are made to the screen, but the screen is not displayed to the user. Thus, as mentioned above, the user is not burdened with viewing numerous screens unnecessarily and bandwidth is saved by not transmitting these screens to the client.

Each of blocks **702-712** also contains a nextscreen tag which determines which screen the user wishes to see. For example, in block **704**, there is a nextscreen tag for "Puborder.search" and for "ready." Depending on the choices selected by the user, an input value of "[pf9]" or an input value of "[pf3]" each corresponding to a function key selection will be sent to the legacy host system such that the appropriate screen may be retrieved. Thus, the requested screen is retrieved without the user needing to know which function keys or keystrokes are required to navigate to the appropriate screen. That information is contained within the macro.

It should be noted that for brevity, ease of explanation, and simplicity, some screens, including the puborder search result screen and the callup address result screen, have been omitted from the macro. It should also be noted that this macro is given merely as an example. Other macros may be created using the methods of the present invention to provide navigation through other legacy host systems. Typically, each legacy host system will have its own macro for navigating through that system, although it is possible to combine each macro for each legacy host system serviced by a server such as server **508** into a single giant macro.

Referring now to **Figure 8**, a flowchart illustrating an overview of a method on a server for navigating and retrieving a legacy host screen is depicted according to the present invention. To start, the server receives a request for a host screen from a client (step **802**). If this is the initial request for the legacy host system by the client, then the client is sent the ready screen containing the hyperlinks to other screens within the legacy host system. Otherwise, the server determines the current screen displayed to the client (step **804**). Next, the server determines whether the host screen to which the user desires access requires variable data to access (step **806**). If it does, then a submittable form with text fields where the appropriate data may be entered by

the user is created and sent to the client (step 808). The server then waits until the data entered by the user is received (step 810).

If the host screen does not require variable data for access or if the variable data has been received from the client, the server enters the appropriate data and commands to acquire access to the host screen navigating through various intermediate screens if necessary (step 812). The host screen is then retrieved (step 814) and the server formats the host screen, including hyperlinks to other screens within the legacy host system, into a markup language, such as, for example, XML or HTML, which can be read by a browser (step 816). The server then sends the newly formatted host screen to the client to be displayed to the user (step 818) at which point the process ends.

Referring now to **Figure 9**, a flowchart illustrating a method of navigating and viewing legacy host screens from the perspective of a client computer is depicted in accordance with the present invention. To start, the user sends a request to the server for access to the legacy host system. The client then receives a formatted legacy host screen containing hyperlinks to the various screens within the legacy host system that the user might wish to view (step 902). Next, the client browser waits for user input (step 904). The browser determines whether a hyperlink (or "hot" link) has been selected by the user (step 906). If not, the browser continues to wait for user input (step 904).

If a hyperlink has been selected by the user, then the browser determines which link has been selected (step 908) and sends a request for the newly selected host screen from the legacy host system to the server (step 910). The browser then waits until it receives from the server the formatted legacy host screen requested by the user (step 912) and then displays this screen to the user (step 914).

This information may be displayed in the bottom half of the window frame in which the navigation screen is located or may be displayed in a separate window frame. The hyperlinks to other screens within the legacy host system may be intermingled and displayed along with the data from the legacy host system or the two may be separated and displayed separately. Other methods of presenting the data from the legacy host system and the navigation tools to the user are also possible and within the scope of the present invention.

It is important to note that while the present invention has been described in the context of a fully functioning data processing system, those of ordinary skill in the art will appreciate that the processes of the present invention are capable of being distributed in a form of a computer readable medium of instructions and a variety of forms and that the present invention applies equally regardless of the particular type of signal bearing media actually used to carry out the distribution. Examples of computer readable media include recordable-type media such a floppy disc, a hard disk drive, a RAM, and CD-ROMs and transmission-type media such as digital and analog communications links.

The description of the present invention has been presented for purposes of illustration and description, but is not intended to be exhaustive or limited to the invention in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art. The embodiment was chosen and described in order to best explain the principles of the invention the practical application and to enable others of ordinary skill in the art to understand the invention for various embodiments with various modifications as are suited to the particular use contemplated.

CLAIMS:

What is claimed is:

1. A method in a data processing system, comprising the steps of:
receiving, from a client, a request for a host screen;
navigating to the host screen;
retrieving the host screen;
formatting the host screen into a formatted host screen; and
sending the formatted host screen to the client.
2. The method as recited in claim 1, wherein the formatted host screen includes selectable links to other screens within a host system.
3. The method as recited in claim 1, wherein the step of navigating to the host screen comprises retrieving at least one intermediate screen in order to retrieve the host screen.
4. The method as recited in claim 1, further comprising:
responsive to a determination that variable data is needed to navigate to the host screen, sending to the client a submittable form containing text fields that may be filled in by a user; and
responsive to receiving the variable data from the client, using the variable data to retrieve the host screen.

1 5. The method as recited in claim 1, wherein the client is a portable data
2 processing system.

1 6. The method as recited in claim 5, wherein the portable data processing system
2 is a wireless system.

1 7. The method as recited in claim 3, wherein the intermediate screen is not
2 presented to the user.

1 8. The method as recited in claim 3, wherein appropriate entries are made in the
2 at least one intermediate screen in order to navigate to the host screen.

1 9. The method as recited in claim 1, wherein the formatting step formats the host
2 screen into a markup language.

1 10. The method as recited in claim 9, wherein the markup language is an
2 extensible markup language.

1 11. The method as recited in claim 9, wherein the markup language is a hypertext
2 markup language.

1 12. A computer program product in computer readable media for use in a data
2 processing system for navigating screens in a legacy host system, the computer
3 program product comprising:

4 first instructions for receiving, from a client, a request for a host screen;
5 second instructions for navigating to the host screen;

6 third instructions for retrieving the host screen;
7 fourth instructions for formatting the host screen into a formatted host screen;
8 and
9 fifth instructions for sending the formatted host screen to the client.

1 13. The computer program product as recited in claim 12, wherein the formatted
2 host screen includes selectable links to other screens within a host system.

1 14. The computer program product as recited in claim 12, wherein the step of
2 navigating to the host screen comprises retrieving at least one intermediate screen in
3 order to retrieve the host screen.

1 15. The computer program product as recited in claim 12, further comprising:
2 sixth instructions, responsive to a determination that variable data is needed to
3 navigate to the host screen, for sending to the client a submittable form containing
4 text fields that may be filled in by a user; and
5 seventh instructions, responsive to receiving the variable data from the client,
6 for using the variable data to retrieve the host screen.

1 16. The computer program product as recited in claim 12, wherein the client is a
2 portable data processing system.

1 17. The computer program product as recited in claim 16, wherein the portable
2 data processing system is a wireless system.

1 18. The computer program product as recited in claim 14, wherein the
2 intermediate screen is not presented to the user.

1 19. The computer program product as recited in claim 14, wherein appropriate
2 entries are made in the at least one intermediate screen in order to navigate to the host
3 screen.

1 20. The computer program product as recited in claim 12, wherein the formatting
2 step formats the host screen into a markup language.

1 21. The computer program product as recited in claim 20, wherein the markup
2 language is an extensible markup language.

1 22. The computer program product as recited in claim 20, wherein the markup
2 language is a hypertext markup language.

1 23. A system for navigating screens in a legacy host system, comprising:
2 means for receiving, from a client, a request for a host screen;
3 means for navigating to the host screen;
4 means for retrieving the host screen;
5 means for formatting the host screen into a formatted host screen; and
6 means for sending the formatted host screen to the client.

1 24. The system as recited in claim 23, wherein the formatted host screen includes
2 selectable links to other screens within a host system.

1 25. The system as recited in claim 23, wherein the step of navigating to the host
2 screen comprises retrieving at least one intermediate screen in order to retrieve the
3 host screen.

1 26. The system as recited in claim 23, further comprising:
2 means, responsive to a determination that variable data is needed to navigate
3 to the host screen, for sending to the client a submittable form containing text fields
4 that may be filled in by a user; and
5 means, responsive to receiving the variable data from the client, for using the
6 variable data to retrieve the host screen.

1 27. The system as recited in claim 23, wherein the client is a portable data
2 processing system.

1 28. The system as recited in claim 5, wherein the portable data processing system
2 is a wireless system.

1 29. The system as recited in claim 25, wherein the intermediate screen is not
2 presented to the user.

1 30. The system as recited in claim 25, wherein appropriate entries are made in the
2 at least one intermediate screen in order to navigate to the host screen.

1 31. The system as recited in claim 23, wherein the formatting step formats the
2 host screen into a markup language.

1 32. The system as recited in claim 31, wherein the markup language is an
2 extensible markup language.

1 33. The system as recited in claim 31, wherein the markup language is a hypertext
2 markup language.

1 34. A macro bean for providing navigation between screens within a legacy host
2 system, the macro bean comprising:

3 first instructions for receiving a request for a requested host screen from a
4 legacy host system;

5 second instructions for determining the current host screen; and

6 third instructions for navigating to the requested host screen.

1 35. The macro bean as recited in claim 34, wherein intermediate host screens
2 between the current host screen and the requested host screen are unsent to a client.

1 36. The macro bean as recited in claim 34, further comprising fourth instructions
2 for entering appropriate data at intermediate host screens in order to access the
3 requested host screen.

1 37. The macro bean as recited in claim 34, wherein variable data received from a
2 client is entered appropriately into one or more of the intermediate host screens.


ABSTRACT OF THE DISCLOSURE

LEGACY HOST SYSTEM HOT LINK MODELING AND NAVIGATION

5 A method and apparatus for navigating screens in a legacy host system. In a preferred embodiment, requests for specific legacy host screens are received by a server. The server then navigates to the appropriate screen within the legacy host system and retrieves the host screen. Any intermediate screens navigated by the server in reaching the host screen are not displayed to the user. If variable data need be entered to access the host screen, the server sends the user a submittable form on which to enter the appropriate information, which, once entered and sent to the server, is used by the server to retrieve the host screen. Once the host screen has been 10 retrieved, the server formats it into a web page format using a hypertext language and sends the screen to the user. Other screens within the legacy host system are accessed by user selection of selectable links displayed to the user.




RSW9-99-108



200
Server

Figure 2

RSW9-99-108



300
Client

Figure 3

RSW9-99-108

User Interface <u>402</u>		
Menus <u>404</u>	Preferences <u>408</u>	Navigation <u>406</u>

Graphical Display <u>418</u>		
Layout <u>420</u>	Rendering <u>422</u>	Window Management <u>424</u>

Language Interpretation <u>412</u>		
HTML <u>414</u>		

Communications (HTTP) <u>410</u>		
-------------------------------------	--	--

400
Figure 4
RSW9-99-108

Browser





Figure 5

RSW9-99-108



600
Figure 6
RSW9-99-108

```
<HASCRIPT name="VMLinks" timeout="50000" >
```

```
<screen name="Ready" transient="false" entryscreen="true" exitscreen="false">
  <description>
    <oia status="NOTINHIBITED" />
    <cursor row="23" col="1" />
    <string value="Ready;" />
  </description>
  <nextscreens>
    <nextscreen name="Puborder.main">
      <input value="puborder[enter]" />
    </nextscreen>
    <nextscreen name="Callup.main">
      <input value="callup[enter]" />
    </nextscreen>
  </nextscreens>
</screen>
```

702

```
<screen name="Puborder.main" transient="false" entryscreen="false" exitscreen="false">
  <description>
    <oia status="NOTINHIBITED" />
    <cursor row="14" col="3" />
  </description>
  <nextscreens>
    <nextscreen name="Puborder.search">
      <input value="[pf9]" />
    </nextscreen>
    <nextscreen name="Ready">
      <input value="[pf3]" />
    </nextscreen>
  </nextscreens>
</screen>
```

704

```
<screen name="Puborder.search" transient="false" entryscreen="false" exitscreen="false">
  <description>
    <oia status="NOTINHIBITED" />
    <cursor row="6" col="18"/>
    <string value="SEARCH WORDS:" />
  </description>
  <nextscreens>
    <nextscreen name="Puborder.main">
      <input value="[pf3]" />
    </nextscreen>
    <nextscreen name="Puborder.search.result">
      <prompt name="Search Words" row="6" col="18" len="32" clearfield="true" />
      <input value="[enter]" />
    </nextscreen>
  </nextscreens>
  <comment>
    Note: the puborder search result screen is not included in this macro for brevity's sake.
  </comment>
</screen>
```

706

Figure 7A

RSW9-99-108

```

<screen name="Callup.main" transient="false" entryscreen="false" exitscreen="false">
  <description>
    <oia status="NOTINHIBITED" />
    <string value="Callup" />
  </description>
  <nextscreens>
    <nextscreen name="Ready">
      <input value="[pf3]" />
    </nextscreen>
    <nextscreen name="Callup.result.main">
      <prompt name="Search Name" row="8" col="32" len="35" clearfield="true" />
      <input value="[enter]" />
    </nextscreen>
  </nextscreens>
</screen>

```

708

```

<screen name="Callup.result.main" transient="false" entryscreen="false" exitscreen="false">
  <description>
    <oia status="NOTINHIBITED" />
    <string value="Callup" />
  </description>
  <nextscreens>
    <nextscreen name="Callup.result.address">
      <input value="a[enter]" />
    </nextscreen>
    <nextscreen name="Callup.main">
      <input value="[pf12]" />
    </nextscreen>
  </nextscreens>
  <comment>
    Note: the callup address result screen is not included in this macro for brevity's sake.
  </comment>
</screen>

```

710

```

<screen name="Puborder.exit" transient="true" entryscreen="false" exitscreen="false">
  <description>
    <oia status="NOTINHIBITED" />
    <cursor row="9" col="14" />
    <string value="Exit Puborder" />
  </description>
  <actions>
    <input value="1[enter]" />
  </actions>
</screen>

```

712

Figure 7B

RSW9-99-108

RSW99108
S. D. Ims, et al
8 of 11

```

<screen name="Need Enter" transient="true" entryscreen="false" exitsscreen="false">
  <description>
    <oia status="NOTINHIBITED" />
    <string value="ENTER to continue..." />
  </description>
  <actions>
    <input value="[enter]" />
  </actions>
</screen>

<screen name="MORE" transient="true" entryscreen="false" exitsscreen="false">
  <description>
    <oia status="NOTINHIBITED" />
    <string value="MORE..." />
  </description>
  <actions>
    <input value="[clear]" row="0" col="0" movecursor="false" xlatehostkeys="true" />
  </actions>
</screen>

<screen name="HOLDING" transient="true" entryscreen="false" exitsscreen="false">
  <description>
    <oia status="NOTINHIBITED" />
    <string value="HOLDING..." />
  </description>
  <actions>
    <input value="[clear]" row="0" col="0" movecursor="false" xlatehostkeys="true" />
  </actions>
</screen>
</HAScript>

```

714

716

718

Figure 7C

RSW9-99-108




Figure 8
RSW9-99-108




Figure 9
RSW9-99-108

Declaration and Power of Attorney for Patent Application

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name; I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

Legacy Host System Hot Link Modeling and Navigation

the specification of which (check one)

☒ is attached hereto.

☐ was filed on _____ as Application Serial No. _____ and was amended on _____.

I hereby state that I have reviewed and understand the contents of the above- identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the patentability of this application in accordance with Title 37, Code of Federal Regulations, §1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s):

Number	Country	Day/Month/Year	Priority Claimed
--------	---------	----------------	------------------

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose information material to the patentability of this application as defined in Title 37, Code of Federal Regulations, §1.56 which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

Prior U.S. Applications:

Serial No.	Filing Date	Status
------------	-------------	--------

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both,

under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

As a named inventor, I hereby appoint the following attorneys and/or agents to prosecute this application and transact all business in the Patent and Trademark Office connected therewith:

J. S. Ray-Yarletts, Reg. No. 39,808; B. A. Clay, Reg. No. 32,121; G. M. Doudnikoff, Reg. No. 32,847; E. H. Duffield, Reg. No. 25,970; J. W. Herndon, Reg. No. 27,901; C. A. Hughes, Reg. No. 26,914; E. A. Pennington, Reg. No. 32,588; J. E. Hoel, Reg. No. 26,279; and J. C. Redmond, Jr., Reg. No. 18,753.

Send all correspondence to: Jeanine S. Ray-Yarletts
IBM Corp., Dept. T81/Bldg. 062
P.O. Box 12195
Research Triangle Park, NC 27709
Phone: 919-543-2541 Fax: 919-254-4330

(1) Inventor: **Steven D. Ims**

Signature:



1999 Nov 17

Date

Residence: 208 Tenbury Wells Drive
Apex, North Carolina 27502


Citizenship: United States of America

Post Office

Address: same as residence

(2) Inventor: **Yongcheng Li**

Signature:



11/17/1999

Date

Residence: 107 Olde Tree Drive
Raleigh, North Carolina 27606

Citizenship: People's Republic of China

Post Office

Address: same as residence

(3) Inventor: **Yih-Shin Tan**

Signature: 

11/17/99

Date


Residence: 300 Gretton Place
Raleigh, North Carolina 27615

Citizenship: United States of America

Post Office

Address: same as residence

(4) Inventor: **Brian Webb**

Signature: 

11/17/1999
Date

Residence: 4608 Pine Tree Drive
Raleigh, North Carolina 27613

Citizenship: United States of America

Post Office

Address: same as residence

608 PINE TREE DRIVE
RALEIGH, NC 27613